



NIKKELVERK

# PLATING NICKEL

## PRODUCT DESCRIPTION AND PACKAGING

### Product Description

Nikkelverk is one of the largest suppliers of electrolytic NICKEL in the world. Through over one hundred years of participation in the industry and the development of NICKEL products to satisfy a wide range of applications, the name Nikkelverk nickel has become synonymous with quality, service and dependability.

Nikkelverk's quality is the result of research and innovative technology and is reflected in the consistent high purity of its NICKEL products.

Nikkelverk Plating Nickel has one of the lowest concentrations of total impurities of any commercially available Nickel.

For use as anodes in electroplating applications, the products are available as whole cathode, 25 mm and 100 mm squares.

Further information and assistance are available upon request and on the webpage [www.glencorexstrata.com](http://www.glencorexstrata.com).


### Typical Analysis

Nickel _____	> 99.98 %
Carbon _____	< 0.002 %
Cobalt _____	< 0.0002 %
Copper _____	< 0.0001 %
Iron _____	< 0.001 %
Lead _____	< 0.0002 %
Sulphur _____	< 0.0002 %
Zinc _____	< 0.0002 %

Nikkelverk NICKEL is guaranteed to meet the chemical requirements of ISO 6283 grade R9995 and ASTM B39-79.

Bulk density of 25 mm and 100 mm squares:  
Approx. 4.3 kg/dm<sup>3</sup> and 3.6 kg/dm<sup>3</sup>

*Safety Data Sheet available upon request.*



The Quality Management System for the production of nickel products at Nikkelverk's refinery located in Kristiansand, Norway is ISO 9001, ISO 14001 and OHSAS 18001 registered.



9145 King Street, Franklin Park, IL 60131  
Tel: 847-678-3952 Fax: 847-678-0758  
*Your source for Glencore Nickel*



NIKKELVERK

NICKEL

## Standard Sizes and Packaging

### 25 mm squares



- 4 x 250 kg steel drums, net weight 1,000 kg, strapped to a skidded wooden pallet.

### 100 mm squares



- 4 x 200 kg steel drums, net weight 800 kg, strapped to a skidded wooden pallet.



- 100 x 10 kg polyethylene bags, net weight 1,000 kg, packed in a skidded wooden box.




- 1,500 kg wooden box.

### Whole Cathode



- 2,000 kg polypropylene bag ("Big bag"), strapped to a wooden pallet.



- 1,280 x 720 mm whole untrimmed cathode, net weight approx. 1,000 kg, strapped to wooden skids.